(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 23 August 2001 (23.08.2001)

PCT

(10) International Publication Number WO 01/61970 A2

(51) International Patent Classification7:

H04M 1/00

- (21) International Application Number: PCT/EP01/01433
- (22) International Filing Date: 9 February 2001 (09.02.2001)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

GE2000A000020 18 February 2000 (18.02.2000)

- (71) Applicant (for all designated States except US): CAL-DANA, Franco [IT/IT]; Via dei Giardini 5, I-40129 Bologna (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): CALDANA, Marcus [SE/IT]; Via dei Giardini 5, I-40129 Bologna (IT).


- (74) Agents: PORSIA, Attilio et al.; Succ. Ing. Fischetti & Weber, Via Caffaro, 3/2, I-16124 Genova (IT).
- (81) Designated States (national): AL, AU, JP, LT, LV, MK, RO, RU, SI, US.
- (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEVICE FOR THE QUICK AND EASY USE OF A SMALL SIZE CELLULAR TELEPHONE



(57) Abstract: The small size cellular telephone (T) is fixed on a telescopic slide (201, 101) sliding on a guide (1) which can be longitudinally secured on the user's arm (B), at the wrist (P). When the cellular telephone calls and has the vibration signaller warning system activated, the vibrations are easily transmitted to the slides and guide system and from this last to the user's wrist who can this way instantaneously notice the call state, even if he is in a noisy place. By catching the cellular telephone with the free hand, the user can extend the guides and quickly bring the cellular telephone itself to the palm of the hand to use it. When the conversation is over, the cellular telephone can be as well quickly taken back to the backward rest position on the wrist. Suitable release means are provided to keep the slides in the backward rest position and if required also in the extended use position of the cellular telephone.

WO 01/61970

WO 01/61970

5

10

15

20

25

10/531368 PCT/EP01/01433

TITLE: "Devision the quick and easy use of a small e cellular telephone" APR 2005

DESCRIPTION

In order to carry about, for the user, cellular telephones or mobile phones, there are actually different types of cases which the user can wear for example at the belt or over one shoulder. No one of the devices actually known allows the possibility of quickly and easily setting the cellular telephone to its use condition and then as well quickly and easily setting it back to rest, and no one of the known devices allows to carry the cellular telephone in such a position to allow the user to hear a call, particularly in presence of great noise. The invention intends to solve these and other problems through the following solution idea. The small size cellular telephone is fixed on a telescopic slide sliding on a guide longitudinally to be secured at the wrist of the arm of the user. In this position, when the cellular telephone receives a call and has the vibration signaller warning system activated, the vibrations are easily transmitted to the slides and guide system and from this latter to the wrist of the user who can this way instantaneously notice the call state, even in a noisy place. By catching the cellular telephone with the free hand, the user can extend the guides and quickly bring the cellular telephone to the palm of the hand to use it. When the conversation is over, the cellular telephone can be as well quickly taken back to the backward rest position on the wrist. Suitable means are provided to keep the slides in the backward rest position and if required also in the extended use position of the cellular telephone. Further features of the invention and the advantages deriving therefrom, will better appear from the following description of a preferred embodiment of same, illustrated, by way of non-limiting example, in the figures of the attached sheets of drawings, in which:

- Figures 1 and 2 show the device in question, longitudinally sectioned, fixed to the user's wrist, and shown respectively in the cellular telephone rest position and use position;
- Figure 3 shows further details of the device taken along the transversal sec-

WO 01/61970 PCT/EP01/01433

- Figure 4 hows, enlarged and longitudinally stooned, the assembly of the guide and telescopic slides, shown in the backward rest position as in Figure 1;

- Figure 5 shows in plan view the rear end of the upper slide of the device as from the details of Figure 4.

5

10

15

20

25

30

From Figures 1, 2 and 3 it can be appreciated that the device includes a rectilinear guide 1, flat shaped and provided at one end on its lower part with any means adapted to be secured longitudinally on the arm B of the user, at the wrist P. For this purpose the guide 1 can be provided on its lower part with a loop 2 passed through by a strap 3 encircling the user's wrist P. The strap 3 can be the same one which, in opposition with the guide 1, retains the wrist watch W. It is understood that differently from what shown, the guide 1 can have on its lower part an anatomic shape and/or can be suitably padded to be worn at the wrist without any problem. Viewed transversally as from Figure 3, the guide 1 has for example a dovetail shape and has a slide 101 sliding longitudinally which in its turn has a transversal dovetail shape and serves as guide for a further flat slide 201 on which there is fixed with longitudinal setting the cellular telephone T, for example by means of small clips 4, 4' engaging grooved zones at the ends of the cellular telephone itself. The cellular telephone has the aerial A turned towards the user's hand. From Figure 1 it can be noticed that when the device is in rest position, the slides 101, 201 are superimposed one onto the other and with respect to the guide 1 and the cellular telephone is in a backward position allowing the user the free use of the hand M. When the cellular telephone calls and has the vibration signaller activated, the vibrations are transmitted to the assembly 1, 101, 201 and from this to the wrist P, so that the user can notice the call state even if he is in a noisy place. From Figure 2 instead, it becomes clear how by taking the cellular telephone T out with the free hand and making the slide assembly 201, 101 slide on the guide 1, the same cellular telephone T comes to be arranged in the palm of the hand M, into a position suitable to use it quickly and easily. With a movement as well quick and easy the cellular telephone can be brought to the rest position of Figure 1. With reference to figures 4 and 5 is now evidenced in detail one possible embodiment of the assembly 1, 101, 201. From said figures it can be no5

10

15

20.

201 is provided on the rear end neengaged by the cellular telephone, with a flexible tongue 5 which has a tooth 105 turned downwards and when the same slide 201 is in the backward rest position, said tooth 105 snaps in a small recess 6 provided on the rear end of the slide 101, at the end of a longitudinal groove 7 of the same slide 101. Pulling longitudinally the slide 201, the tooth 105 cooperates with the flared inner edge 106 of the recess 6 and easily gets out of said recess, while the tongue 5 bends. The tooth 105 then slips on the bottom of the groove 7 and finally snaps into a recess 8 identical and opposed to the recess 6 mentioned above. Keeping the longitudinal pull on the slide 201, its tooth 105 which has reached the end of the groove 7, drags the slide 101 below making it slide on the guide 1. Also the slide 101 is provided in the rear part with a flexible tongue 9, analogous to the tongue 5, whose tooth 109 gets out of a recess 10, analogous to the recess 6 and slides in a longitudinal groove 11, analogous to the groove 7, at whose end it is provided a recess 12, analogous to the recess 8, where said tooth 109 snaps. It is then clear how the slide assembly 101, 201 steadily remains in the backward rest position thanks to the co-operation of the teeth 105 and 109 with the recesses 6 and 10 and how, on the contrary, it steadily remains in the extended position thanks to the co-operation of the same teeth 105 and 109 with the recesses 8 and 12. Reference numerals 108, 110, 112 indicate the flared inner edges of the recesses 8, 10, 12, analogous to the edge 106 of the recess 6.

1. A device for the quick and easy use of a small size cellular telephone (T), characterised in that it includes a rectilinear guide (1) fixed by any suitable means and with longitudinal setting on the initial portion of the user's arm (B), at the wrist (P), on said guide there being assembled at least one longitudinally sliding slide (201) on which the cellular telephone (T) is longitudinally placed, turned with the aerial (A) towards the user's hand, means being provided to keep the slide with the cellular telephone in rear position on said guide and to allow the extension of the same slide, so that the part of it carrying the cellular telephone can reach the palm of the hand of the user, to allow the use of the cellular telephone.

5

10

15

20

25

30

- 2. A device according to claim 1, in which on the guide (1) there is mounted an assembly of telescopic slides (10, 201) on the last of which the cellular telephone (T) is assembled, the whole so to contain the dimension in length of the guide and slide assembly, although maintaining a remarkable extendibility of the slides themselves, means being provided to keep in the rear position said telescopic slide assembly.
- 3. A device according to the preceding claims, in which the cellular telephone (T) is fixed on the slide (201) by means of small clips (4, 4').
- 4. A device according to the preceding claims, in which the assembly of the guide (1) and of the telescopic slides (101, 201) is characterised by a slidable coupling of the dovetail type.
- 5. A device according to the preceding claims, characterised in that the slides (201, 101) are provided, in connection with their rear end, with longitudinal and flexible tongues (5, 9), with lower teeth (105, 109) which slide with friction in longitudinal grooves (7, 11) of the same slides, which with their ends lock the teeth and their slides in the end positions of the strokes of extension and retraction.
- 6. A device according to claim 5, in which at the end of the bottom of the lon-gitudinal grooves (7, 11) of the slides (101, 201), there are provided recesses (6, 8 and 10, 12) within which snap the lower teeth (105, 109) of said flexible tongues (5, 9), to keep the same slides in the retracted rest position and the extended use posi-

WO 01/61970 PCT/EP01/01433


tion of the cellulatelephone.

5




7. A device according to claim 6, in which the teeth (105, 109) of the flexible tongues (5, 9) and/or the inner edges (106, 108, 110, 112) of the recesses (6, 8, 10, 12) within which snap the said teeth at the end of strokes of extension and of retraction of the slides (101, 201), are flared to help the disengagement of the same teeth from said recesses.

- 8. A device according to the preceding claims characterised in that it can be fixed onto the user's wrist (P) through a strap (3) wrapping the wrist itself.
- 9. A device according to claim 7, in which the strap (3) fixing the device itself onto the user's wrist carries also a watch (W).



PCT/EP01/01433 10/531368



2/2





Fig. 5





(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 23 August 2001 (23.08.2001)

PCT

(10) International Publication Number WO 01/61970 A3

(51) International Patent Classification7: H04M 1/02

H04B 1/38.

(74) Agents: PORSIA, Attilio et al.; Succ. Ing. Fischetti & Weber, Via Caffaro, 3/2, I-16124 Genova (IT).

(21) International Application Number:

PCT/EP01/01433

(81) Designated States (national): AL, AU, JP, LT, LV, MK, RO, RU, SI, US.

(22) International Filing Date: 9 February 2001 (09.02.2001)

(84) Designated States (regional): European patent (AT. BE,

(25) Filing Language:

(26) Publication Language:

English English CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

(30) Priority Data:

18 February 2000 (18.02.2000) GE2000A000020

Published:

with international search report

(71) Applicant (for all designated States except US): CAL-DANA, Franco [IT/IT]; Via dei Giardini 5, I-40129 Bologna (IT).


(88) Date of publication of the international search report: 18 April 2002

(72) Inventor; and

(75) Inventor/Applicant (for US only): CALDANA, Marcus [SE/IT]; Via dei Giardini 5, I-40129 Bologna (IT).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEVICE FOR THE QUICK AND EASY USE OF A SMALL SIZE CELLULAR TELEPHONE



(57) Abstract: The small size cellular telephone (T) is fixed on a telescopic slide (201, 101) sliding on a guide (1) which can be longitudinally secured on the user's arm (B), at the wrist (P). When the cellular telephone calls and has the vibration signaller warning system activated, the vibrations are easily transmitted to the slides and guide system and from this last to the user's wrist who can this way instantaneously notice the call state, even if he is in a noisy place. By catching the cellular telephone with the free hand, the user can extend the guides and quickly bring the cellular telephone itself to the palm of the hand to use it. When the conversation is over, the cellular telephone can be as well quickly taken back to the backward rest position on the wrist. Suitable release means are provided to keep the slides in the backward rest position and if required also in the extended use position of the cellular telephone.



	I' TERNATIONAL SEARCH REPORT	International Application No		
		PCT/EP 01/01433		
A. CLASSIF IPC 7	H04B1/38 · H04M1/02			
According to	International Patent Classification (IPC) or to both national classification and IPC			
	SEARCHED SEARCHED			
IPC 7	cumentation searched (classification system followed by classification symbols) H04B H04M			
Documentali	ion searched other than minimum documentation to the extent that such documents ar	e included in the fields searched		
	ata base consulted during the international search (name of data base and, where pra	actical, search terms used)		
C. DOCUME	ENTS CONSIDERED TO BE RELEVANT			
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No		
A	US 5 467 324 A (HOULIHAN JOHN T) 14 November 1995 (1995-11-14) column 1, line 54 -column 2, line 14; figures 4,9,12	1-9		
A	WO 99 59314 A (KAMBE KAORUKO ;KAMBE TAKAO (JP); KAMBE KIMIHITO (JP)) 18 November 1999 (1999-11-18) abstract; figures 3-8	1-9		
A	EP 0 871 236 A (NOKIA MOBILE PHONES LTD) 14 October 1998 (1998-10-14) abstract; figures 8,12	1-9		
Furt	ther documents are listed in the continuation of box C.	family members are listed in annex.		
A docum	or priority d	ent published after the international filing date late and not in conflict with the application but derstand the principle or theory underlying the		

- 'E' earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of mailing of the international search report

Date of the actual completion of the international search

22 August 2001

23 August 2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2

NL - 2280 HV Rijswijk

Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,

Fax: (+31-70) 340-3016

30/08/2001

Authorized officer

Andersen, J.G.

I' 'ERNATIONAL SEARCH REPORT

Information on patent family members

International Application No PCT/EP 01/01433

Patent document cited in search report		Publication date	Patent farmy member(s)		Publication date
US 5467324	Α	14-11-1995	NONE		
WO 9959314	Α	18-11-1999	AU 168899	9 A	29-11-1999
EP 0871236	Α	14-10-1998	FI 97152 US 600552		12-10-1998 21-12-1999

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☑ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
\square COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
□ other.

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.